

MODELS: 30FID

STYLE: Linear

| DESCRIPTION | FEATURES |
|--|---|
| The ultimate in sensible luxury. The I-Series 30FIDL is an insert that uses co-linear venting with 3" flexible chimney liner. Efficiency ratings so good, fans are optional! You must add a faceplate to your order to complete the I-Series 30FIDL installation | <ul style="list-style-type: none"> • Black rectangular door with ceramic glass • Integrated door screen • Snap-lock door for access to the firebox • Remote flame level adjustment • Highly efficient firebox design • Decorative faceplate • Remote control operation • Hidden pilot design • Battery backup for continuous operation • Concealed ribbon burner, in-burner accent lighting, porcelain panels |

| GLASS | |
|---------------------|-----------------------------|
| Viewing Area | 24 1/4" wide x 14 1/4" high |
| Type | Ceramic glass |

| VENTING | |
|-----------------|-----------------------------|
| Size | 3"x3" Co-linear Direct Vent |
| Location | Top |

| GAS | |
|-------------------------------|----------------------|
| Max BTU Natural Gas | 24,000 BTU/hr |
| Max BTU Propane | 23,000 BTU/hr |
| Nominal Inlet pressure | 3.5" w.c. / 10" w.c. |
| Control System | Proflame 2 IPI |
| Burner Style | Linear |

| COMPONENTS | |
|--------------------------|---|
| Power Venting | N/A |
| Electrical | 115 VAC, 60Hz |
| Clearances | Sides: 7 7/8", Back: 10", Top: 16", Floor: 0" |
| Control | Proflame 2 remote control |
| Testing standards | ANSI Z21.50/ CSA 2.22-2014 and ANSI Z21.97/ CSA 2.41-2014 |
| Media options | Firestones, fireglass, speckled stones, driftwood logset |