

MODELS: 34FID

STYLE: Linear Insert

DESCRIPTION	FEATURES
The ultimate in sensible luxury. The I-Series 34FIDL is an insert that uses co-linear venting with 3" flexible chimney liner. Efficiency ratings so good, fans are optional! You must add a faceplate to your order to complete the I-Series 34FIDL installation	<ul style="list-style-type: none"> • Black rectangular door with ceramic glass • Integrated door screen • Snap-lock door for access to the firebox • Remote flame level adjustment • Highly efficient firebox design • Decorative faceplate • Remote control operation • Hidden pilot design • Battery backup for continuous operation • Concealed ribbon burner, in burner accent lighting, + porcelain panels

GLASS	
Viewing Area	28 3/8" wide x 18 1/8" high
Type	Ceramic glass

VENTING	
Size	3"x3" Co-linear Direct Vent
Location	Top

GAS	
Max BTU Natural Gas	31,000 BTU/hr
Max BTU Propane	30,000 BTU/hr
Nominal Inlet pressure	3.5" w.c. / 10" w.c.
Control System	Proflame 2 IPI
Burner Style	Concealed Linear

COMPONENTS	
Power Venting	N/A
Electrical	115 VAC, 60Hz
Clearances	Sides: 8 1/2", Back: 10", Top: 23", Floor: 0"
Control	Proflame 2 remote control
Testing standards	ANSI Z21.50/ CSA 2.22-2014 and ANSI Z21.97/ CSA 2.41-2014
Media options	Firestones, fireglass, speckled stones, driftwood logset