

MODELS: Distinction D6315ST

STYLE: See Through

| DESCRIPTION | FEATURES |
|--|---|
| <p>The D6315 is a full load single sided direct vent fireplace characterized by a generous landscape viewing area and linear burner. The concealed burner allows the burner to be covered with glass or stone media. Additional features underneath the burner include multicolor LED lighting and a standard circulating fan kit.</p> | <ul style="list-style-type: none"> • Clean face design • 50,000 BTU/HR NG or LP • Montigo 4TH generation linear concealed burner • Ceramic glass door • 50% turn down gas valve with stepper motor • IPI Electronic Ignition • Power vent compatible Full Feature Proflame 2 remote control • Quiet circulating fans with remote speed adjustment • Ceramic glass reflective liner, multicolor LED lighting, star ice fireglass • Invisimesh screens |

| GLASS | |
|---------------------|-------------------------|
| Viewing Area | 63" wide x 14 3/8" high |
| Type | Ceramic glass |

| VENTING | |
|-----------------|-------------------|
| Size | 5"/8" Direct Vent |
| Location | Top middle |

| GAS | |
|-------------------------------|--------------------------------|
| Max BTU Natural Gas | 50,000 BTU/hr |
| Max BTU Propane | 50,000 BTU/hr |
| Nominal Inlet pressure | 3.8" w.c. / 11" w.c. |
| Control System | Proflame 2 IPI |
| Burner Style | Concealed linear ribbon burner |

| COMPONENTS | |
|--------------------------|---|
| Power Venting | Optional, Montigo roof mount, wall mount or inline power vent |
| Electrical | 120 VAC, 60 Hz, 1Ph, 5A |
| Clearances | Sides: 3 1/3", Back: 2", Top: 38 1/4", Floor: 0" |
| Control | Proflame 2 remote control, LED lighting remote control |
| Testing standards | ANSI Z21.50/ CSA 2.22-2014 and ANSI Z21.97/ CSA 2.41-2014 |
| Media options | Firestones, fireglass, speckled stones, driftwood logset |