

MODEL: C6200DD
STYLE: Single Sided Outdoor

DESCRIPTION

The C-View Series commercial fireplace and its associated components are part of an engineered system. Please contact Montigo to confirm if your installation requirements are within the parameters of these standard specifications. This system is available with Power COOL-Pack technology, which is optional for residential applications, but required in public use applications. All C-View Series systems are power vented with multiple options available. All C-View Series systems are tested and certified to current ANSI Standards with CSA International US and Canada.

All C-View Series systems are customizable – contact Montigo today to customize a system that meets your needs.

GLASS	
Viewing Area	72" wide x 20" – 60" high *CUSTOM SIZES AVAILABLE
Type	5 mm or 6 mm thick tempered glass
Temperature	Power COOL-Pack < 115°F
No Glass	Open units are available, please contact Montigo for additional information
INTAKE / EXHAUST	
Intake Location	Front, below glass
Power Vent	Integrally built into the system
GAS	
Input	95,000 BTU/hr, ½" NPT gas line connection
Minimum Inlet Pressure	5.5" w.c. Natural Gas OR 11" w.c. Propane
Control Valves	One Honeywell Smart Valve SV9501 with hot surface pilot Q3450
Burner Style	Concealed Burner with 8" ribbon flame or 18" high-low flame
MISCELLANEOUS	
Electrical	208 VAC+ Neutral, single phase, dedicated circuit, amp size determined by specific system requirements
Testing Standards	ANSI Z21.50/ CSA 2.22-2014 and ANSI Z21.97/ CSA 2.41-2014
Construction	Full stainless steel construction
Accessory Options	Traditional logset, driftwood logset, ceramic stones, glass media, LED lighting, reflective glass panels