

**MODEL:** C7200DD  
**STYLE:** Single Sided Outdoor

**DESCRIPTION**

The C-View Series commercial fireplace and its associated components are part of an engineered system. Please contact Montigo to confirm if your installation requirements are within the parameters of these standard specifications. This system is available with Power COOL-Pack technology, which is optional for residential applications, but required in public use applications. All C-View Series systems are power vented with multiple options available. All C-View Series systems are tested and certified to current ANSI Standards with CSA International US and Canada.

All C-View Series systems are customizable – contact Montigo today to customize a system that meets your needs.

<b>GLASS</b>	
<b>Viewing Area</b>	84" wide x 20" – 60" high *CUSTOM SIZES AVAILABLE
<b>Type</b>	5 mm or 6 mm thick tempered glass
<b>Temperature</b>	Power COOL-Pack < 115°F
<b>No Glass</b>	Open units are available, please contact Montigo for additional information
<b>INTAKE / EXHAUST</b>	
<b>Intake Location</b>	Front, below glass
<b>Power Vent</b>	Integrally built into the system
<b>GAS</b>	
<b>Input</b>	125,000 BTU/hr, ½" NPT gas line connection
<b>Minimum Inlet Pressure</b>	5.5" w.c. Natural Gas OR 11" w.c. Propane
<b>Control Valves</b>	One Honeywell Smart Valve SV9501 with hot surface pilot Q3450
<b>Burner Style</b>	Concealed Burner with 8" ribbon flame or 18" high-low flame
<b>MISCELLANEOUS</b>	
<b>Electrical</b>	208 VAC+ Neutral, single phase, dedicated circuit, amp size determined by specific system requirements
<b>Testing Standards</b>	ANSI Z21.50/ CSA 2.22-2014 and ANSI Z21.97/ CSA 2.41-2014
<b>Construction</b>	Full stainless steel construction
<b>Accessory Options</b>	Traditional logset, driftwood logset, ceramic stones, glass media, LED lighting, reflective glass panels