

MODEL: CFPO-R2
STYLE: Round Firepit

DESCRIPTION

The commercial firepit and its associated components are part of an engineered system. Please contact Montigo to confirm if your installation requirements are within the parameters of these standard specifications. All firepit systems are tested and certified to current ANSI Standards with CSA International US and Canada.

All firepit systems are customizable – contact Montigo today to customize a system that meets your needs.

DIMENSIONS

Burner Area 24" Diameter *CUSTOM SIZES AVAILABLE
No Glass Open units are available, please contact Montigo for additional information

INTAKE

Intake Size Total 13 square inches minimum
Intake Location Bottom

EXHAUST

Venting Unvented outdoor appliance

GAS

Input 80,000 BTU/hr, ½" NPT gas line connection
Minimum Inlet Pressure 5.5" w.c. Natural Gas OR 11" w.c. Propane
Control Valves One Honeywell Smart Valve SV9501 with hot surface pilot Q3450
Burner Style Concealed Burner with 8" ribbon flame

MISCELLANEOUS

Electrical 120 VAC, single phase, dedicated circuit, amp size determined by specific system requirements
Testing Standards ANSI Z21.97/ CSA 2.41-2014
Construction Full stainless steel construction or black satin painted galvanized steel
Accessory Options Glass media