



MODEL: CFPO-5

STYLE: Outdoor Fire Pit

DESCRIPTION

The C-View Series commercial fireplace and its associated components are part of an engineered system. Please contact Montigo to confirm if your installation requirements are within the parameters of these standard specifications. All C-View Series systems are tested and certified to current ANSI Standards with CSA International US and Canada.

All C-View Series systems are customizable – contact Montigo today to customize a system that meets your needs.

DIMENSIONS	
Burner Area	15.88" x 64" *CUSTOM SIZES AVAILABLE
No Glass	Open units are available, please contact Montigo for additional information
INTAKE	
Intake Size	Total 13.33 square inches minimum
Intake Location	Bottom
EXHAUST	
Venting	Unvented outdoor appliance
GAS	
Input	80,000 BTU/hr, ½" NPT gas line connection
	80,000 BTU/hr, ½" NPT gas line connection 5.5" w.c. Natural Gas OR 11"w.c. Propane
Input	
Input Minimum Inlet Pressure	5.5" w.c. Natural Gas OR 11"w.c. Propane
Input Minimum Inlet Pressure Control Valves	5.5" w.c. Natural Gas OR 11"w.c. Propane One Honeywell Smart Valve SV9501 with hot surface pilot Q3450
Input Minimum Inlet Pressure Control Valves	5.5" w.c. Natural Gas OR 11"w.c. Propane One Honeywell Smart Valve SV9501 with hot surface pilot Q3450
Input Minimum Inlet Pressure Control Valves Burner Style	5.5" w.c. Natural Gas OR 11"w.c. Propane One Honeywell Smart Valve SV9501 with hot surface pilot Q3450
Input Minimum Inlet Pressure Control Valves Burner Style MISCELLANEOUS	5.5" w.c. Natural Gas OR 11"w.c. Propane One Honeywell Smart Valve SV9501 with hot surface pilot Q3450 Concealed Burner with 8" ribbon flame
Input Minimum Inlet Pressure Control Valves Burner Style MISCELLANEOUS Electrical	5.5" w.c. Natural Gas OR 11"w.c. Propane One Honeywell Smart Valve SV9501 with hot surface pilot Q3450 Concealed Burner with 8" ribbon flame 120 VAC, single phase, dedicated circuit, amp size determined by specific system requirements